

2008 RAM BASE WEIGHTS/GCW/PAYLOAD/TRAILER TOW

3500

**SELECT AN OPTION BELOW*

REGULAR CAB

 140.5"WB 4x2


 140.5"WB 4x4

QUAD CAB

 140.5"WB 4x2

 140.5"WB 4x4

 160.5"WB 4x2

 160.5"WB 4x4

MEGA CAB

 160.5"WB 4x2

 160.5"WB 4x4

2008 RAM BASE WEIGHTS/GCW/PAYLOAD 3500

NOTE : BASE WEIGHTS CAN CHANGE

REGULAR CAB 140.5"WB 4x2

RAM REGULAR CAB 3500 140.5"WB 2WD LONG BRD - ST													D1 3L62 (DRW)		FOR BOX DELETE SEE NOTE BELOW	
Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail				
5.7L V8 Gas (EZA)	M6	POSG56 6 sp MANU (DEG)	4.10	11,000	5,150	5,851	3,024	2,827	4,110	9,350	17,000	11,000				
5.7L V8 Gas (EZA)	A5	545RFE 5 sp AUTO (DGQ)	4.10	11,000	5,210	5,794	2,979	2,815	4,110	9,350	17,000	11,050				
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.42	11,500	4,720	6,781	3,938	2,843	4,750	9,350	19,000	12,050				
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.73	11,500	4,720	6,781	3,938	2,843	4,750	9,350	21,000	14,050				
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	3.73	11,500	4,790	6,712	3,880	2,832	4,750	9,350	21,000	14,150				
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	4.10	11,500	4,790	6,712	3,880	2,832	4,750	9,350	23,000	16,150				

RAM REGULAR CAB 3500 140.5"WB 2WD LONG BRD - SLT													D1 3H62 (DRW)		FOR BOX DELETE SEE NOTE BELOW	
Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail				
5.7L V8 Gas (EZA)	M6	POSG56 6 sp MANU (DEG)	4.10	11,000	5,120	5,884	3,053	2,831	4,110	9,350	17,000	10,950				
5.7L V8 Gas (EZA)	A5	545RFE 5 sp AUTO (DGQ)	4.10	11,000	5,170	5,827	3,008	2,819	4,110	9,350	17,000	11,000				
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.42	11,500	4,690	6,814	3,968	2,847	4,750	9,350	19,000	12,050				
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.73	11,500	4,690	6,814	3,968	2,847	4,750	9,350	21,000	14,050				
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	3.73	11,500	4,750	6,745	3,910	2,836	4,750	9,350	21,000	14,100				
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	4.10	11,500	4,750	6,745	3,910	2,836	4,750	9,350	23,000	16,100				

NOTES:

Note that all the payload and Max Trail weights are ESTIMATED values.

1. Payload is rounded to the nearest 10 lbs. Payload = GVWR - Curb Wt.
2. Maximum trailer weights are rounded to the nearest 50 lbs.
Maximum Trailer Weight = GCWR - Curb wt. -150 lbs. (allowance for driver)

NOTE: GVW FOR 3500 BOX DELETE DUAL REAR WHEEL (XBC) IS 11,500 FOR 4x4 AND 11,000 FOR 4x2

OPTIONS

2008 RAM BASE WEIGHTS/GCW/PAYLOAD 3500

NOTE : BASE WEIGHTS CAN CHANGE

REGULAR CAB 140.5"WB 4x4

RAM REGULAR CAB 3500 140.5"WB 4WD LONG BRD - ST												D1 8L62 (DRW)		FOR BOX DELETE SEE NOTE BELOW	
Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail			
5.7L V8 Gas (EZA)	M6	POSG56 6 sp MANU (DEG)	4.10	11,500	5,080	6,424	3,527	2,898	5,200	9,350	17,000	10,450			
5.7L V8 Gas (EZA)	A5	545RFE 5 sp AUTO (DGQ)	4.10	11,500	5,130	6,368	3,472	2,897	5,200	9,350	17,000	10,500			
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.42	12,200	5,050	7,147	4,275	2,872	5,200	9,350	19,000	11,700			
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.73	12,200	5,050	7,147	4,275	2,872	5,200	9,350	21,000	13,700			
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	3.73	12,200	5,120	7,083	4,213	2,870	5,200	9,350	21,000	13,750			
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	4.10	12,200	5,120	7,083	4,213	2,870	5,200	9,350	24,000	16,750			

RAM REGULAR CAB 3500 140.5"WB 4WD LONG BRD - SLT												D1 8H62 (DRW)		FOR BOX DELETE SEE NOTE BELOW	
Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail			
5.7L V8 Gas (EZA)	M6	POSG56 6 sp MANU (DEG)	4.10	11,500	5,040	6,461	3,557	2,904	5,200	9,350	17,000	10,400			
5.7L V8 Gas (EZA)	A5	545RFE 5 sp AUTO (DGQ)	4.10	11,500	5,090	6,405	3,502	2,903	5,200	9,350	17,000	10,450			
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.42	12,200	5,020	7,184	4,305	2,879	5,200	9,350	19,000	11,650			
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.73	12,200	5,020	7,184	4,305	2,879	5,200	9,350	21,000	13,650			
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	3.73	12,200	5,080	7,120	4,243	2,877	5,200	9,350	21,000	13,750			
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	4.10	12,200	5,080	7,120	4,243	2,877	5,200	9,350	24,000	16,750			

NOTES:

Note that all the payload and Max Trail weights are ESTIMATED values.

1. Payload is rounded to the nearest 10 lbs. Payload = GVWR - Curb Wt.
2. Maximum trailer weights are rounded to the nearest 50 lbs.
Maximum Trailer Weight = GCWR - Curb wt. -150 lbs. (allowance for driver)

NOTE: GVW FOR 3500 BOX DELETE DUAL REAR WHEEL (XBC) IS 11,500 FOR 4x4 AND 11,000 FOR 4x2



2008 RAM BASE WEIGHTS/GCW/PAYLOAD 3500

09/01/2007

NOTE : BASE WEIGHTS CAN CHANGE

QUAD CAB 140.5"WB 4x2

RAM QUAD CAB 3500 140.5"WB 2WD SHORT BRD - ST						D1 3L41 (SRW)						
Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.42	10,100	3,560	6,542	3,898	2,644	4,750	6,200	19,000	12,300
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.73	10,100	3,560	6,542	3,898	2,644	4,750	6,200	21,000	14,300
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	3.73	10,100	3,620	6,478	3,844	2,634	4,750	6,200	21,000	14,350
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	4.10	10,100	3,620	6,478	3,844	2,634	4,750	6,200	23,000	16,350

RAM QUAD CAB 3500 140.5"WB 2WD SHORT BRD - SLT						D1 3H41 (SRW)						
Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.42	10,100	3,470	6,629	3,966	2,664	4,750	6,200	19,000	12,200
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.73	10,100	3,470	6,629	3,966	2,664	4,750	6,200	21,000	14,200
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	3.73	10,100	3,530	6,565	3,912	2,654	4,750	6,200	21,000	14,300
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	4.10	10,100	3,530	6,565	3,912	2,654	4,750	6,200	23,000	16,300

RAM QUAD CAB 3500 140.5"WB 2WD SHORT BRD - LARAMIE						D1 3P41 (SRW)						
Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.42	10,100	3,360	6,742	4,039	2,704	4,750	6,200	19,000	12,100
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.73	10,100	3,360	6,742	4,039	2,704	4,750	6,200	21,000	14,100
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	3.73	10,100	3,420	6,678	3,985	2,694	4,750	6,200	21,000	14,150
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	4.10	10,100	3,420	6,678	3,985	2,694	4,750	6,200	23,000	16,150

NOTES:

Note that all the payload and Max Trail weights are ESTIMATED values.

1. Payload is rounded to the nearest 10 lbs. Payload = GVWR - Curb Wt.
2. Maximum trailer weights are rounded to the nearest 50 lbs.
Maximum Trailer Weight = GCWR - Curb wt. -150 lbs. (allowance for driver).

 **OPTIONS**

 **Site Map**

 **Main Menu**

PRINT

 **ALL**

 **IN**

 **OUT**

2008 RAM BASE WEIGHTS/GCW/PAYLOAD 3500

09/01/2007

NOTE : BASE WEIGHTS CAN CHANGE

QUAD CAB 140.5"WB 4x4

RAM QUAD CAB 3500 140.5"WB 4WD SHORT BRD - ST						D1 8L41 (SRW)						
Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.42	10,100	3,110	6,990	4,294	2,696	5,200	6,200	19,000	11,850
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.73	10,100	3,110	6,990	4,294	2,696	5,200	6,200	21,000	13,850
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	3.73	10,100	3,170	6,926	4,232	2,694	5,200	6,200	21,000	13,900
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	4.10	10,100	3,170	6,926	4,232	2,694	5,200	6,200	24,000	16,900

RAM QUAD CAB 3500 140.5"WB 4WD SHORT BRD - SLT						D1 8H41 (SRW)						
Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.42	10,100	3,010	7,092	4,381	2,711	5,200	6,200	19,000	11,750
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.73	10,100	3,010	7,092	4,381	2,711	5,200	6,200	21,000	13,750
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	3.73	10,100	3,070	7,028	4,319	2,709	5,200	6,200	21,000	13,800
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	4.10	10,100	3,070	7,028	4,319	2,709	5,200	6,200	24,000	16,800

RAM QUAD CAB 3500 140.5"WB 4WD SHORT BRD - LARAMIE						D1 8P41 (SRW)						
Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.42	10,100	2,900	7,197	4,444	2,753	5,200	6,200	19,000	11,650
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.73	10,100	2,900	7,197	4,444	2,753	5,200	6,200	21,000	13,650
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	3.73	10,100	2,970	7,133	4,382	2,751	5,200	6,200	21,000	13,700
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	4.10	10,100	2,970	7,133	4,382	2,751	5,200	6,200	24,000	16,700

NOTES:

Note that all the payload and Max Trail weights are ESTIMATED values.

1. Payload is rounded to the nearest 10 lbs. Payload = GVWR - Curb Wt.
2. Maximum trailer weights are rounded to the nearest 50 lbs.
Maximum Trailer Weight = GCWR - Curb wt. -150 lbs. (allowance for driver)



2008 RAM BASE WEIGHTS/GCW/PAYLOAD 3500

09/01/2007

NOTE : BASE WEIGHTS CAN CHANGE

QUAD CAB 160.5"WB 4x2

RAM QUAD CAB 3500 160.5"WB 2WD LONG BRD - ST				D1 3L42 (DRW)			FOR BOX DELETE SEE NOTE BELOW					
Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail
5.7L V8 Gas (EZA)	M6	POSG56 6 sp MANU (DEG)	4.10	11,000	4,870	6,134	3,210	2,924	4,110	9,350	17,000	10,700
5.7L V8 Gas (EZA)	A5	545RFE 5 sp AUTO (DGQ)	4.10	11,000	4,910	6,091	3,167	2,924	4,110	9,350	17,000	10,750
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.42	11,500	4,410	7,092	4,093	2,999	4,750	9,350	19,000	11,750
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.73	11,500	4,410	7,092	4,093	2,999	4,750	9,350	21,000	13,750
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	3.73	11,500	4,480	7,023	4,035	2,988	4,750	9,350	21,000	13,850
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	4.10	11,500	4,480	7,023	4,035	2,988	4,750	9,350	23,000	15,850

RAM QUAD CAB 3500 160.5"WB 2WD LONG BRD - ST				D1 3L42 (SRW)								
Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.42	10,100	3,390	6,715	4,050	2,664	4,750	6,200	19,000	12,150
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.73	10,100	3,390	6,715	4,050	2,664	4,750	6,200	21,000	14,150
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	3.73	10,100	3,470	6,633	3,991	2,641	4,750	6,200	21,000	14,200
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	4.10	10,100	3,470	6,633	3,991	2,641	4,750	6,200	23,000	16,200

RAM QUAD CAB 3500 160.5"WB 2WD LONG BRD - SLT				D1 3H42 (DRW)			FOR BOX DELETE SEE NOTE BELOW					
Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail
5.7L V8 Gas (EZA)	M6	POSG56 6 sp MANU (DEG)	4.10	11,000	4,800	6,200	3,260	2,940	4,110	9,350	17,000	10,650
5.7L V8 Gas (EZA)	A5	545RFE 5 sp AUTO (DGQ)	4.10	11,000	4,840	6,157	3,217	2,940	4,110	9,350	17,000	10,700
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.42	11,500	4,340	7,158	4,143	3,014	4,750	9,350	19,000	11,700
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.73	11,500	4,340	7,158	4,143	3,014	4,750	9,350	21,000	13,700
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	3.73	11,500	4,420	7,076	4,084	2,991	4,750	9,350	21,000	13,750
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	4.10	11,500	4,420	7,076	4,084	2,991	4,750	9,350	23,000	15,750

RAM QUAD CAB 3500 160.5"WB 2WD LONG BRD - SLT				D1 3H42 (SRW)								
Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.42	10,100	3,310	6,790	4,105	2,684	4,750	6,200	19,000	12,050
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.73	10,100	3,310	6,790	4,105	2,684	4,750	6,200	21,000	14,050
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	3.73	10,100	3,390	6,708	4,046	2,661	4,750	6,200	21,000	14,150
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	4.10	10,100	3,390	6,708	4,046	2,661	4,750	6,200	23,000	16,150

NOTES:

- Note that all the payload and Max Trail weights are ESTIMATED values.
1. Payload is rounded to the nearest 10 lbs. Payload = GVWR - Curb Wt.
 2. Maximum trailer weights are rounded to the nearest 50 lbs.
Maximum Trailer Weight = GCWR - Curb wt. -150 lbs. (allowance for driver)

NOTE: GVW FOR 3500 BOX DELETE DUAL REAR WHEEL (XBC) IS 11,500 FOR 4x4 AND 11,000 FOR 4x2



2008 RAM BASE WEIGHTS/GCW/PAYLOAD 3500

NOTE : BASE WEIGHTS CAN CHANGE

QUAD CAB 160.5"WB 4x2 - CONTINUED

RAM QUAD CAB 3500 160.5"WB 2WD LONG BRD - LARAMIE						D1 3P42 (DRW)		FOR BOX DELETE SEE NOTE BELOW				
Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail
5.7L V8 Gas (EZA)	M6	POSG56 6 sp MANU (DEG)	4.10	11,000	4,700	6,298	3,316	2,982	4,110	9,350	17,000	10,550
5.7L V8 Gas (EZA)	A5	545RFE 5 sp AUTO (DGQ)	4.10	11,000	4,750	6,255	3,273	2,982	4,110	9,350	17,000	10,600
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.42	11,500	4,260	7,240	4,180	3,060	4,750	9,350	19,000	11,600
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.73	11,500	4,260	7,240	4,180	3,060	4,750	9,350	21,000	13,600
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	3.73	11,500	4,340	7,158	4,121	3,037	4,750	9,350	21,000	13,700
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	4.10	11,500	4,340	7,158	4,121	3,037	4,750	9,350	23,000	15,700

RAM QUAD CAB 3500 160.5"WB 2WD LONG BRD - LARAMIE						D1 3P42 (SRW)						
Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.42	10,100	3,230	6,872	4,142	2,730	4,750	6,200	19,000	12,000
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.73	10,100	3,230	6,872	4,142	2,730	4,750	6,200	21,000	14,000
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	3.73	10,100	3,310	6,790	4,083	2,707	4,750	6,200	21,000	14,050
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	4.10	10,100	3,310	6,790	4,083	2,707	4,750	6,200	23,000	16,050

NOTES:

Note that all the payload and Max Trail weights are ESTIMATED values.

1. Payload is rounded to the nearest 10 lbs. Payload = GVWR - Curb Wt.
2. Maximum trailer weights are rounded to the nearest 50 lbs.
Maximum Trailer Weight = GCWR - Curb wt. -150 lbs. (allowance for driver)

NOTE: GVW FOR 3500 BOX DELETE DUAL REAR WHEEL (XBC) IS 11,500 FOR 4x4 AND 11,000 FOR 4x2



2008 RAM BASE WEIGHTS/GCW/PAYLOAD 3500

09/01/2007

NOTE : BASE WEIGHTS CAN CHANGE

QUAD CAB 160.5"WB 4x4

RAM QUAD CAB 3500 160.5"WB 4WD LONG BRD - ST						D1 8L42 (DRW)		FOR BOX DELETE SEE NOTE BELOW				
Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail
5.7L V8 Gas (EZA)	M6	POSG56 6 sp MANU (DEG)	4.10	11,500	4,960	6,537	3,584	2,953	5,200	9,350	17,000	10,300
5.7L V8 Gas (EZA)	A5	545RFE 5 sp AUTO (DGQ)	4.10	11,500	5,030	6,471	3,526	2,945	5,200	9,350	17,000	10,400
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.42	12,200	4,710	7,492	4,466	3,026	5,200	9,350	19,000	11,350
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.73	12,200	4,710	7,492	4,466	3,026	5,200	9,350	21,000	13,350
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	3.73	12,200	4,780	7,418	4,401	3,017	5,200	9,350	21,000	13,450
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	4.10	12,200	4,780	7,418	4,401	3,017	5,200	9,350	24,000	16,450

RAM QUAD CAB 3500 160.5"WB 4WD LONG BRD ST						D1 8L42 (SRW)						
Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.42	10,100	2,970	7,134	4,422	2,712	5,200	6,200	19,000	11,700
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.73	10,100	2,970	7,134	4,422	2,712	5,200	6,200	21,000	13,700
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	3.73	10,100	3,040	7,060	4,357	2,703	5,200	6,200	21,000	13,800
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	4.10	10,100	3,040	7,060	4,357	2,703	5,200	6,200	24,000	16,800

RAM QUAD CAB 3500 160.5"WB 4WD LONG BRD - SLT						D1 8H42 (DRW)		FOR BOX DELETE SEE NOTE BELOW				
Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail
5.7L V8 Gas (EZA)	M6	POSG56 6 sp MANU (DEG)	4.10	11,500	4,900	6,603	3,634	2,968	5,200	9,350	17,000	10,250
5.7L V8 Gas (EZA)	A5	545RFE 5 sp AUTO (DGQ)	4.10	11,500	4,960	6,537	3,576	2,960	5,200	9,350	17,000	10,300
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.42	12,200	4,640	7,558	4,516	3,042	5,200	9,350	19,000	11,300
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.73	12,200	4,640	7,558	4,516	3,042	5,200	9,350	21,000	13,300
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	3.73	12,200	4,720	7,484	4,451	3,033	5,200	9,350	21,000	13,350
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	4.10	12,200	4,720	7,484	4,451	3,033	5,200	9,350	24,000	16,350

RAM QUAD CAB 3500 160.5"WB 4WD LONG BRD - SLT						D1 8H42 (SRW)						
Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.42	10,100	2,890	7,209	4,477	2,732	5,200	6,200	19,000	11,650
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.73	10,100	2,890	7,209	4,477	2,732	5,200	6,200	21,000	13,650
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	3.73	10,100	2,970	7,135	4,412	2,723	5,200	6,200	21,000	13,700
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	4.10	10,100	2,970	7,135	4,412	2,723	5,200	6,200	24,000	16,700

NOTES:

Note that all the payload and Max Trail weights are ESTIMATED values.

1. Payload is rounded to the nearest 10 lbs. Payload = GVWR - Curb Wt.
2. Maximum trailer weights are rounded to the nearest 50 lbs.
Maximum Trailer Weight = GCWR - Curb wt. -150 lbs. (allowance for driver)

NOTE: GVW FOR 3500 BOX DELETE DUAL REAR WHEEL (XBC) IS 11,500 FOR 4x4 AND 11,000 FOR 4x2

 **NEXT**

 **OPTIONS**

 **Site Map**

 **Main Menu**

PRINT

 **ALL**

 **+**
IN

 **-**
OUT

2008 RAM BASE WEIGHTS/GCW/PAYLOAD 3500

09/01/2007

NOTE : BASE WEIGHTS CAN CHANGE

QUAD CAB 160.5"WB 4x4 - CONTINUED

RAM QUAD CAB 3500 160.5"WB 4WD LONG BRD - LARAMIE						D1 8P42 (DRW)						
Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail
5.7L V8 Gas (EZA)	M6	POSG56 6 sp MANU (DEG)	4.10	11,500	4,790	6,709	3,714	2,996	5,200	9,350	17,000	10,150
5.7L V8 Gas (EZA)	A5	545RFE 5 sp AUTO (DGQ)	4.10	11,500	4,860	6,643	3,656	2,988	5,200	9,350	17,000	10,200
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.42	12,200	4,540	7,664	4,595	3,069	5,200	9,350	19,000	11,200
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.73	12,200	4,540	7,664	4,595	3,069	5,200	9,350	21,000	13,200
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	3.73	12,200	4,610	7,590	4,530	3,060	5,200	9,350	21,000	13,250
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	4.10	12,200	4,610	7,590	4,530	3,060	5,200	9,350	24,000	16,250

RAM QUAD CAB 3500 160.5"WB 4WD LONG BRD - LARAMIE						D1 8P42 (SRW)						
Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.42	10,100	2,780	7,315	4,557	2,759	5,200	6,200	19,000	11,550
6.7L 24V Turbo Diesel (ETJ)	M6	POSG56 6 sp MANU (DEG)	3.73	10,100	2,780	7,315	4,557	2,759	5,200	6,200	21,000	13,550
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	3.73	10,100	2,860	7,241	4,492	2,750	5,200	6,200	21,000	13,600
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	4.10	10,100	2,860	7,241	4,492	2,750	5,200	6,200	24,000	16,600

NOTES:

1. Payload is rounded to the nearest 10 lbs. Payload = GVWR - Curb Wt.
2. Maximum trailer weights are rounded to the nearest 50 lbs.
Maximum Trailer Weight = GCWR - Curb wt. -150 lbs. (allowance for driver)

 **BACK**

 **OPTIONS**

 **Site Map**

 **Main Menu**

PRINT

 **ALL**

 **IN**

 **OUT**

2008 RAM BASE WEIGHTS/GCW/PAYLOAD 3500

09/01/2007

NOTE : BASE WEIGHTS CAN CHANGE

MEGA CAB 160.5"WB 4x2

RAM MEGA CAB 3500 160.5"WB 2WD SHORT BED SLT D1 3H81 (SRW)

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail
6.7L 24V Turbo Diesel (ETJ)	M6	POS G56-6 6sp MANU (DEG)	3.42	10,100	3,070	7,029	4,176	2,853	4,750	6,200	19,000	11,800
6.7L 24V Turbo Diesel (ETJ)	M6	POS G56-6 6sp MANU (DEG)	3.73	10,100	3,070	7,029	4,176	2,853	4,750	6,200	21,000	13,800
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	3.73	10,100	3,150	6,946	4,117	2,829	4,750	6,200	21,000	13,900
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	4.10	10,100	3,150	6,946	4,117	2,829	4,750	6,200	23,000	15,900

RAM MEGA CAB 3500 160.5"WB 2WD SHORT BED SLT D1 3H81 (DRW)

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail
6.7L 24V Turbo Diesel (ETJ)	M6	POS G56-6 6sp MANU (DEG)	3.42	10,500	3,110	7,388	4,213	3,174	4,750	9,350	19,000	11,450
6.7L 24V Turbo Diesel (ETJ)	M6	POS G56-6 6sp MANU (DEG)	3.73	10,500	3,110	7,388	4,213	3,174	4,750	9,350	21,000	13,450
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	3.73	10,500	3,200	7,305	4,154	3,150	4,750	9,350	21,000	13,550
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	4.10	10,500	3,200	7,305	4,154	3,150	4,750	9,350	23,000	15,550

RAM MEGA CAB 3500 160.5"WB 2WD SHORT BED LARAMIE D1 3P81 (SRW)

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail
6.7L 24V Turbo Diesel (ETJ)	M6	POS G56-6 6sp MANU (DEG)	3.42	10,100	3,050	7,047	4,213	2,833	4,750	6,200	19,000	11,800
6.7L 24V Turbo Diesel (ETJ)	M6	POS G56-6 6sp MANU (DEG)	3.73	10,100	3,050	7,047	4,213	2,833	4,750	6,200	21,000	13,800
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	3.73	10,100	3,140	6,964	4,154	2,809	4,750	6,200	21,000	13,900
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	4.10	10,100	3,140	6,964	4,154	2,809	4,750	6,200	23,000	15,900

RAM MEGA CAB 3500 160.5"WB 2WD SHORT BED LARAMIE D1 3P81 (DRW)

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail
6.7L 24V Turbo Diesel (ETJ)	M6	POS G56-6 6sp MANU (DEG)	3.42	10,500	3,040	7,460	4,279	3,181	4,750	9,350	19,000	11,400
6.7L 24V Turbo Diesel (ETJ)	M6	POS G56-6 6sp MANU (DEG)	3.73	10,500	3,040	7,460	4,279	3,181	4,750	9,350	21,000	13,400
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	3.73	10,500	3,120	7,377	4,220	3,157	4,750	9,350	21,000	13,450
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	4.10	10,500	3,120	7,377	4,220	3,157	4,750	9,350	23,000	15,450

Note that all the payload and Max Trail weights are ESTIMATED values.
 1. Payload is rounded to the nearest 10 lbs. Payload = GVWR - Curb Wt.
 2. Maximum trailer weights are rounded to the nearest 50 lbs.
 Maximum Trailer Weight = GCWR - Curb wt. -150 lbs. (allowance for driver)



2008 RAM BASE WEIGHTS/GCW/PAYLOAD 3500

NOTE : BASE WEIGHTS CAN CHANGE

MEGA CAB 160.5"WB 4x4

RAM MEGA CAB 3500 160.5"WB 4WD SHORT BED SLT													D1 8H81 (SRW)	
Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail		
6.7L 24V Turbo Diesel (ETJ)	M6	POS G56-6 6sp MANU (DEG)	3.42	10,100	2,660	7,442	4,537	2,905	5,200	6,200	19,000	11,400		
6.7L 24V Turbo Diesel (ETJ)	M6	POS G56-6 6sp MANU (DEG)	3.73	10,100	2,660	7,442	4,537	2,905	5,200	6,200	21,000	13,400		
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	3.73	10,100	2,730	7,372	4,475	2,897	5,200	6,200	21,000	13,500		
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	4.10	10,100	2,730	7,372	4,475	2,897	5,200	6,200	24,000	16,500		

RAM MEGA CAB 3500 160.5"WB 4WD SHORT BED SLT													D1 8H81 (DRW)	
Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail		
6.7L 24V Turbo Diesel (ETJ)	M6	POS G56-6 6sp MANU (DEG)	3.42	10,500	2,700	7,801	4,575	3,226	5,200	9,350	19,000	11,050		
6.7L 24V Turbo Diesel (ETJ)	M6	POS G56-6 6sp MANU (DEG)	3.73	10,500	2,700	7,801	4,575	3,226	5,200	9,350	21,000	13,050		
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	3.73	10,500	2,770	7,731	4,513	3,218	5,200	9,350	21,000	13,100		
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	4.10	10,500	2,770	7,731	4,513	3,218	5,200	9,350	24,000	16,100		

RAM MEGA CAB 3500 160.5"WB 4WD SHORT BED LARAMIE													D1 8P81 (SRW)	
Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail		
6.7L 24V Turbo Diesel (ETJ)	M6	POS G56-6 6sp MANU (DEG)	3.42	10,100	2,630	7,474	4,567	2,907	5,200	6,200	19,000	11,400		
6.7L 24V Turbo Diesel (ETJ)	M6	POS G56-6 6sp MANU (DEG)	3.73	10,100	2,630	7,474	4,567	2,907	5,200	6,200	21,000	13,400		
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	3.73	10,100	2,700	7,404	4,505	2,899	5,200	6,200	21,000	13,450		
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	4.10	10,100	2,700	7,404	4,505	2,899	5,200	6,200	24,000	16,450		

RAM MEGA CAB 3500 160.5"WB 4WD SHORT BED LARAMIE													D1 8P81 (DRW)	
Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail		
6.7L 24V Turbo Diesel (ETJ)	M6	POS G56-6 6sp MANU (DEG)	3.42	10,500	2,610	7,888	4,633	3,255	5,200	9,350	19,000	10,950		
6.7L 24V Turbo Diesel (ETJ)	M6	POS G56-6 6sp MANU (DEG)	3.73	10,500	2,610	7,888	4,633	3,255	5,200	9,350	21,000	12,950		
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	3.73	10,500	2,680	7,818	4,571	3,247	5,200	9,350	21,000	13,050		
6.7L 24V Turbo Diesel (ETJ)	A6	68RFE 6 sp AUTO (DG7)	4.10	10,500	2,680	7,818	4,571	3,247	5,200	9,350	24,000	16,050		

Note that all the payload and Max Trail weights are ESTIMATED values.
 1. Payload is rounded to the nearest 10 lbs. Payload = GVWR - Curb Wt.
 2. Maximum trailer weights are rounded to the nearest 50 lbs.
 Maximum Trailer Weight = GCWR - Curb wt. -150 lbs. (allowance for driver)

