

2011 RAM BASE WEIGHTS/GCW/PAYLOAD/TRAILER TOW

1500

**SELECT AN OPTION BELOW*

REGULAR CAB

- 120.5"WB 4x2
- 120.5"WB 4x4

- 140.5"WB 4x2
- 140.5"WB 4x4

QUAD CAB

- 140.5"WB 4x2
- 140.5"WB 4x4

CREW CAB

- 140.5"WB 4x2
- 140.5"WB 4x4

- 140.5"WB 4x2
WITH RAM BOX
- 140.5"WB 4x4
WITH RAM BOX



2011 RAM BASE WEIGHTS/GCW/PAYLOAD 1500

NOTE : BASE WEIGHTS CAN CHANGE

REGULAR CAB 120.5"WB 4X2

Std Cab - Short box 4x2 - ST													DS 1L61	
Tire	Engine	Trans Type	Transmission	Axle	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer	
							Total	Front	Rear	Front	Rear			
P265/70R17	3.7L V6 (EKG)	A4	42RLE (DGV) 4 SPD AUTO	3.55	6,025	1,450	4548	2,534	2,014	3,700	3,900	8,500	3,750	
P265/70R17	3.7L V6 (EKG)	A4	42RLE (DGV) 4 SPD AUTO	3.92	6,025	1,450	4548	2,534	2,014	3,700	3,900	8,500	3,750	
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,025	1,300	4,699	2,684	2,015	3,700	3,900	12,500	7,600	
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,025	1,300	4,699	2,684	2,015	3,700	3,900	12,500	7,600	
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,025	1,300	4,699	2,684	2,015	3,700	3,900	12,500	7,600	
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,025	1,300	4,699	2,684	2,015	3,700	3,900	12,500	7,600	
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.21	6,200	1,430	4,742	2,752	1,990	3,700	3,900	12,000	7,050	
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,200	1,430	4,742	2,752	1,990	3,700	3,900	14,000	9,050	
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,200	1,430	4,742	2,752	1,990	3,700	3,900	14,000	9,050	
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.21	6,200	1,430	4,742	2,752	1,990	3,700	3,900	12,000	7,050	
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,200	1,430	4,742	2,752	1,990	3,700	3,900	14,000	9,050	
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,200	1,430	4,742	2,752	1,990	3,700	3,900	14,000	9,050	
Std Cab - Short box 4x2 - SLT / TRX													DS 1H61	
Tire	Engine	Trans Type	Transmission	Axle	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer	
							Total	Front	Rear	Front	Rear			
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,025	1,340	4,656	2,659	1,997	3,700	3,900	12,500	7,650	
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,025	1,340	4,656	2,659	1,997	3,700	3,900	12,500	7,650	
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,025	1,340	4,656	2,659	1,997	3,700	3,900	12,500	7,650	
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,025	1,340	4,656	2,659	1,997	3,700	3,900	12,500	7,650	
P275/60R20	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,025	1,290	4,711	2,690	2,021	3,700	3,900	12,500	7,600	
P275/60R20	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,025	1,290	4,711	2,690	2,021	3,700	3,900	12,500	7,600	
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.21	6,200	1,460	4,715	2,734	1,981	3,700	3,900	12,000	7,100	
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,200	1,460	4,715	2,734	1,981	3,700	3,900	14,000	9,100	
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,200	1,460	4,715	2,734	1,981	3,700	3,900	14,000	9,100	
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.21	6,200	1,460	4,715	2,734	1,981	3,700	3,900	12,000	7,100	
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,200	1,460	4,715	2,734	1,981	3,700	3,900	14,000	9,100	
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,200	1,460	4,715	2,734	1,981	3,700	3,900	14,000	9,100	
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.21	6,200	1,400	4,770	2,764	2,006	3,700	3,900	12,000	7,050	
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,200	1,400	4,770	2,764	2,006	3,700	3,900	14,000	9,050	
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,200	1,400	4,770	2,764	2,006	3,700	3,900	14,000	9,050	
Std Cab - Short box 4x2 - R/T													DS 1S61	
Tire	Engine	Trans Type	Transmission	Axle	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer	
							Total	Front	Rear	Front	Rear			
285/40R22	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	4.1	6,200	1,340	4,839	2,790	2,049	3,700	3,900	10,000	5,000	

NOTES:

Note that all the payload and Max Trail weights are ESTIMATED values.

1. Payload is rounded down to the nearest 10 lbs. Payload = GVWR - Curb Wt.
2. Maximum trailer weights are rounded down to the nearest 50 lbs.
Maximum Trailer Weight = GCWR - Curb wt. -150 lbs. (allowance for driver) - 20 lbs. (variation allowance)
3. The recommended tongue weight is between 10 percent and 15 percent of the gross trailer weight. However, the maximum tongue weight on Class III (the bumper ball) is limited to 500 pounds, and Class IV (the receiver hitch) to 1,045 pounds. Additionally, the GAWR's and GVWR's should never be exceeded.
4. The maximum trailer weight is 5,000 pounds for a weight-carrying hitch. A weight distributing system is recommended for trailers over 5,000 pounds.



2011 RAM BASE WEIGHTS/GCW/PAYLOAD 1500

NOTE : BASE WEIGHTS CAN CHANGE

REGULAR CAB 120.5"WB 4x4

Std Cab - Short box 4x4 - ST DS 6L61													
Tire	Engine	Trans Type	Transmission	Axle	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
							Total	Front	Rear	Front	Rear		
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,350	1,440	4,881	2,846	2,035	3,900	3,900	12,500	7,400
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,350	1,440	4,881	2,846	2,035	3,900	3,900	12,500	7,400
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,350	1,440	4,881	2,846	2,035	3,900	3,900	12,500	7,400
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,350	1,440	4,881	2,846	2,035	3,900	3,900	12,500	7,400
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,350	1,420	4,909	2,880	2,029	3,900	3,900	14,000	8,900
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,350	1,420	4,909	2,880	2,029	3,900	3,900	14,000	8,900
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,350	1,420	4,909	2,880	2,029	3,900	3,900	14,000	8,900
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,350	1,420	4,909	2,880	2,029	3,900	3,900	14,000	8,900
Std Cab - Short box 4x4 - SLT / TRX DS 6H61													
Tire	Engine	Trans Type	Transmission	Axle	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
							Total	Front	Rear	Front	Rear		
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,350	1,490	4,830	2,777	2,054	3,900	3,900	12,500	7,450
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,350	1,490	4,830	2,777	2,054	3,900	3,900	12,500	7,450
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,350	1,490	4,830	2,777	2,054	3,900	3,900	12,500	7,450
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,350	1,490	4,830	2,777	2,054	3,900	3,900	12,500	7,450
P275/60R20	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,350	1,440	4,885	2,807	2,078	3,900	3,900	12,500	7,400
P275/60R20	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,350	1,440	4,885	2,807	2,078	3,900	3,900	12,500	7,400
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,350	1,440	4,890	2,851	2,038	3,900	3,900	14,000	8,900
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,350	1,440	4,890	2,851	2,038	3,900	3,900	14,000	8,900
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,350	1,440	4,890	2,851	2,038	3,900	3,900	14,000	8,900
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,350	1,440	4,890	2,851	2,038	3,900	3,900	14,000	8,900
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,350	1,380	4,945	2,882	2,063	3,900	3,900	14,000	8,850
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,350	1,380	4,945	2,882	2,063	3,900	3,900	14,000	8,850
Std Cab - Short box 4x4 - SPORT DS 6S61													
Tire	Engine	Trans Type	Transmission	Axle	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
							Total	Front	Rear	Front	Rear		
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,350	1,350	4,977	2,883	2,094	3,900	3,900	14,000	8,850
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,350	1,350	4,977	2,883	2,094	3,900	3,900	14,000	8,850

NOTES:

Note that all the payload and Max Trail weights are ESTIMATED values.

1. Payload is rounded down to the nearest 10 lbs. Payload = GVWR - Curb Wt.

2. Maximum trailer weights are rounded down to the nearest 50 lbs.

Maximum Trailer Weight = GCWR - Curb wt. -150 lbs. (allowance for driver) - 20 lbs. (variation allowance)

3. The recommended tongue weight is between 10 percent and 15 percent of the gross trailer weight. However, the maximum tongue weight on Class III (the bumper ball) is limited to 500 pounds, and Class IV (the receiver hitch) to 1,045 pounds. Additionally, the GAWR's and GVWR's should never be exceeded.

4. The maximum trailer weight is 5,000 pounds for a weight-carrying hitch. A weight distributing system is recommended for trailers over 5,000 pounds.



2011 RAM BASE WEIGHTS/GCW/PAYLOAD 1500

NOTE : BASE WEIGHTS CAN CHANGE

REGULAR CAB 140.5"WB 4x2

Std Cab - Long box 4x2 - ST DS 1L62													
Tire	Engine	Trans Type	Transmission	Axle	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
							Total	Front	Rear	Front	Rear		
P265/70R17	3.7L V6 (EKG)	A4	42RLE (DGV) 4 SPD AUTO	3.55	6,600	1,860	4718	2,667	2,051	3,700	3,900	8,500	3,600
P265/70R17	3.7L V6 (EKG)	A4	42RLE (DGV) 4 SPD AUTO	3.92	6,600	1,860	4718	2,667	2,051	3,700	3,900	8,500	3,600
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,600	1,700	4874	2,841	2,033	3,700	3,900	12,500	7,450
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,600	1,700	4874	2,841	2,033	3,700	3,900	12,500	7,450
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,600	1,700	4,874	2,841	2,033	3,700	3,900	12,500	7,450
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,600	1,700	4,874	2,841	2,033	3,700	3,900	12,500	7,450
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.21	6,600	1,660	4919	2,884	2,035	3,700	3,900	12,000	6,900
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,600	1,660	4919	2,884	2,035	3,700	3,900	14,000	8,900
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,600	1,660	4919	2,884	2,035	3,700	3,900	15,500	10,400
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.21	6,600	1,660	4,919	2,884	2,035	3,700	3,900	12,000	6,900
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,600	1,660	4,919	2,884	2,035	3,700	3,900	14,000	8,900
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,600	1,660	4,919	2,884	2,035	3,700	3,900	15,500	10,400
Std Cab - Long box 4x2 - SLT / TRX DS 1H62													
Tire	Engine	Trans Type	Transmission	Axle	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
							Total	Front	Rear	Front	Rear		
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,600	1,730	4,845	2,811	2,034	3,700	3,900	12,500	7,450
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,600	1,730	4,845	2,811	2,034	3,700	3,900	12,500	7,450
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,600	1,730	4,845	2,811	2,034	3,700	3,900	12,500	7,450
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,600	1,730	4,845	2,811	2,034	3,700	3,900	12,500	7,450
P275/60R20	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,600	1,690	4,888	2,836	2,052	3,700	3,900	12,500	7,400
P275/60R20	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,600	1,690	4,888	2,836	2,052	3,700	3,900	12,500	7,400
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.21	6,600	1,670	4,903	2,846	2,057	3,700	3,900	12,000	6,900
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,600	1,670	4,903	2,846	2,057	3,700	3,900	14,000	8,900
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,600	1,670	4,903	2,846	2,057	3,700	3,900	15,500	10,450
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.21	6,600	1,670	4,903	2,846	2,057	3,700	3,900	12,000	6,900
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,600	1,670	4,903	2,846	2,057	3,700	3,900	14,000	8,900
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,600	1,670	4,903	2,846	2,057	3,700	3,900	15,500	10,400
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.21	6,600	1,630	4,946	2,871	2,075	3,700	3,900	12,000	6,850
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,600	1,630	4,946	2,871	2,075	3,700	3,900	14,000	8,850
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,600	1,630	4,946	2,871	2,075	3,700	3,900	15,500	10,350

NOTES:

Note that all the payload and Max Trail weights are ESTIMATED values.

1. Payload is rounded down to the nearest 10 lbs. Payload = GVWR - Curb Wt.

2. Maximum trailer weights are rounded down to the nearest 50 lbs.

Maximum Trailer Weight = GCWR - Curb wt. -150 lbs. (allowance for driver) - 20 lbs. (variation allowance)

3. The recommended tongue weight is between 10 percent and 15 percent of the gross trailer weight. However, the maximum tongue weight on Class III (the bumper ball) is limited to 500 pounds, and Class IV (the receiver hitch) to 1,045 pounds. Additionally, the GAWR's and GVWR's should never be exceeded.

4. The maximum trailer weight is 5,000 pounds for a weight-carrying hitch. A weight distributing system is recommended for trailers over 5,000 pounds.



2011 RAM BASE WEIGHTS/GCW/PAYLOAD 1500

NOTE : BASE WEIGHTS CAN CHANGE

REGULAR CAB 140.5"WB 4x4

Std Cab - Long box 4x4 - ST														DS 6L62													
Tire	Engine	Trans Type	Transmission	Axle	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer														
							Total	Front	Rear	Front	Rear																
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,600	1,540	5,039	2,958	2,081	3,900	3,900	12,500	7,250														
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,600	1,540	5,039	2,958	2,081	3,900	3,900	12,500	7,250														
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,600	1,540	5,039	2,958	2,081	3,900	3,900	12,500	7,250														
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,600	1,540	5,039	2,958	2,081	3,900	3,900	12,500	7,250														
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,600	1,510	5,067	2,992	2,076	3,900	3,900	14,000	8,750														
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,600	1,510	5,067	2,992	2,076	3,900	3,900	15,500	10,250														
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,600	1,510	5,067	2,992	2,076	3,900	3,900	14,000	8,750														
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,600	1,510	5,067	2,992	2,076	3,900	3,900	15,500	10,250														
Std Cab - Long box 4x4 - SLT / TRX														DS 6H62													
Tire	Engine	Trans Type	Transmission	Axle	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer														
							Total	Front	Rear	Front	Rear																
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,600	1,560	5,019	2,929	2,091	3,900	3,900	12,500	7,300														
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,600	1,560	5,019	2,929	2,091	3,900	3,900	12,500	7,300														
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,600	1,560	5,019	2,929	2,091	3,900	3,900	12,500	7,300														
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,600	1,560	5,019	2,929	2,091	3,900	3,900	12,500	7,300														
P275/60R20	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,600	1,510	5,062	2,953	2,109	3,900	3,900	12,500	7,250														
P275/60R20	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,600	1,510	5,062	2,953	2,109	3,900	3,900	12,500	7,250														
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,600	1,530	5,048	2,963	2,085	3,900	3,900	14,000	8,750														
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,600	1,530	5,048	2,963	2,085	3,900	3,900	15,500	10,250														
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,600	1,530	5,048	2,963	2,085	3,900	3,900	14,000	8,750														
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,600	1,530	5,048	2,963	2,085	3,900	3,900	15,500	10,250														
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,600	1,480	5,091	2,987	2,103	3,900	3,900	14,000	8,700														
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,600	1,480	5,091	2,987	2,103	3,900	3,900	15,500	10,200														

NOTES:
 Note that all the payload and Max Trail weights are ESTIMATED values.
 1. Payload is rounded down to the nearest 10 lbs. Payload = GVWR - Curb Wt.
 2. Maximum trailer weights are rounded down to the nearest 50 lbs.
 Maximum Trailer Weight = GCWR - Curb wt. -150 lbs. (allowance for driver) - 20 lbs. (variation allowance)
 3. The recommended tongue weight is between 10 percent and 15 percent of the gross trailer weight. However, the maximum tongue weight on Class III (the bumper ball) is limited to 500 pounds, and Class IV (the receiver hitch) to 1,045 pounds. Additionally, the GAWR's and GVWR's should never be exceeded.
 4. The maximum trailer weight is 5,000 pounds for a weight-carrying hitch. A weight distributing system is recommended for trailers over 5,000 pounds.



2011 RAM BASE WEIGHTS/GCW/PAYLOAD 1500

09/01/2010

NOTE : BASE WEIGHTS CAN CHANGE
QUAD CAB 140.5"WB 4x2

Quad Cab 4x2 - ST												DS 1L41				
Tire	Engine	Trans Type	Transmission	Axle	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer			
							Total	Front	Rear	Front	Rear					
P265/70R17	3.7L V6 (EKG)	A4	42RLE (DGV) 4 SPD AUTO	3.55	6,700	1,810	4870	2,717	2,153	3,700	3,900	8,500	3,450			
P265/70R17	3.7L V6 (EKG)	A4	42RLE (DGV) 4 SPD AUTO	3.92	6,700	1,810	4870	2,717	2,153	3,700	3,900	8,500	3,450			
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,700	1,670	5,008	2,858	2,150	3,700	3,900	12,500	7,300			
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,700	1,670	5,008	2,858	2,150	3,700	3,900	12,500	7,300			
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,700	1,670	5,008	2,858	2,150	3,700	3,900	12,500	7,300			
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,700	1,670	5,008	2,858	2,150	3,700	3,900	12,500	7,300			
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.21	6,700	1,620	5,058	2,902	2,156	3,700	3,900	12,000	6,750			
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,700	1,620	5,058	2,902	2,156	3,700	3,900	14,000	8,750			
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,700	1,620	5,058	2,902	2,156	3,700	3,900	15,500	10,250			
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.21	6,700	1,620	5,058	2,902	2,156	3,700	3,900	12,000	6,750			
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,700	1,620	5,058	2,902	2,156	3,700	3,900	14,000	8,750			
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,700	1,620	5,058	2,902	2,156	3,700	3,900	15,500	10,250			
Quad Cab 4x2 - SLT / TRX / BIG HORN / LONE STAR												DS 1H41				
Tire	Engine	Trans Type	Transmission	Axle	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer			
							Total	Front	Rear	Front	Rear					
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,700	1,660	5,015	2,870	2,145	3,700	3,900	12,500	7,300			
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,700	1,660	5,015	2,870	2,145	3,700	3,900	12,500	7,300			
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,700	1,660	5,015	2,870	2,145	3,700	3,900	12,500	7,300			
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,700	1,660	5,015	2,870	2,145	3,700	3,900	12,500	7,300			
P275/60R20	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,700	1,620	5,058	2,894	2,163	3,700	3,900	12,500	7,250			
P275/60R20	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,700	1,620	5,058	2,894	2,163	3,700	3,900	12,500	7,250			
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.21	6,700	1,610	5,064	2,913	2,151	3,700	3,900	12,000	6,750			
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,700	1,610	5,064	2,913	2,151	3,700	3,900	14,000	8,750			
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,700	1,610	5,064	2,913	2,151	3,700	3,900	15,500	10,250			
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.21	6,700	1,610	5,064	2,913	2,151	3,700	3,900	12,000	6,750			
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,700	1,610	5,064	2,913	2,151	3,700	3,900	14,000	8,750			
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,700	1,610	5,064	2,913	2,151	3,700	3,900	15,500	10,250			
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.21	6,700	1,570	5,107	2,938	2,169	3,700	3,900	12,000	6,700			
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,700	1,570	5,107	2,938	2,169	3,700	3,900	14,000	8,700			
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,700	1,570	5,107	2,938	2,169	3,700	3,900	15,500	10,200			
Quad Cab 4x2 - SPORT												DS 1S41				
Tire	Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer			
							Total	Front	Rear	Front	Rear					
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.21	6,700	1,610	5,163	2,940	2,223	3,700	3,900	12,000	6,650			
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,700	1,610	5,163	2,940	2,223	3,700	3,900	14,000	8,650			
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,700	1,610	5,163	2,940	2,223	3,700	3,900	15,500	10,150			
Quad Cab 4x2 - LARAMIE												DS 1P41				
Tire	Engine	Trans Type	Transmission	Axle	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer			
							Total	Front	Rear	Front	Rear					
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.21	6,700	1,610	5,252	2,992	2,260	3,700	3,900	12,000	6,550			
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,700	1,610	5,252	2,992	2,260	3,700	3,900	14,000	8,550			
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,700	1,610	5,252	2,992	2,260	3,700	3,900	15,500	10,050			
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.21	6,700	1,610	5,252	2,992	2,260	3,700	3,900	12,000	6,550			
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,700	1,610	5,252	2,992	2,260	3,700	3,900	14,000	8,550			
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,700	1,610	5,252	2,992	2,260	3,700	3,900	15,500	10,050			
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.21	6,700	1,570	5,316	3,019	2,298	3,700	3,900	12,000	6,500			
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,700	1,570	5,316	3,019	2,298	3,700	3,900	14,000	8,500			
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,700	1,570	5,316	3,019	2,298	3,700	3,900	15,500	10,000			

NOTES:

Note that all the payload and Max Trail weights are ESTIMATED values.

1. Payload is rounded down to the nearest 10 lbs. Payload = GVWR - Curb Wt.
2. Maximum trailer weights are rounded down to the nearest 50 lbs.
 Maximum Trailer Weight = GCWR - Curb wt. -150 lbs. (allowance for driver) - 20 lbs. (variation allowance)
3. The recommended tongue weight is between 10 percent and 15 percent of the gross trailer weight. However, the maximum tongue weight on Class III (the bumper ball) is limited to 500 pounds, and Class IV (the receiver hitch) to 1,045 pounds. Additionally, the GAWR's and GVWR's should never be exceeded.
4. The maximum trailer weight is 5,000 pounds for a weight-carrying hitch. A weight distributing system is recommended for trailers over 5,000 pounds.



2011 RAM BASE WEIGHTS/GCW/PAYLOAD 1500

NOTE : BASE WEIGHTS CAN CHANGE
QUAD CAB 140.5"WB 4x4

Quad Cab 4x4 - ST DS 6L41													
Tire	Engine	Trans Type	Transmission	Axle	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
							Total	Front	Rear	Front	Rear		
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,700	1,610	5,178	3,001	2,178	3,900	3,900	12,500	7,150
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,700	1,610	5,178	3,001	2,178	3,900	3,900	12,500	7,150
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,700	1,610	5,178	3,001	2,178	3,900	3,900	12,500	7,150
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,700	1,610	5,178	3,001	2,178	3,900	3,900	12,500	7,150
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,700	1,610	5,236	3,052	2,184	3,900	3,900	14,000	8,550
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,700	1,610	5,236	3,052	2,184	3,900	3,900	15,500	10,050
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,700	1,440	5,236	3,052	2,184	3,900	3,900	14,000	8,550
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,700	1,440	5,236	3,052	2,184	3,900	3,900	15,500	10,050
Quad Cab 4x4 - SLT / TRX / BIG HORN / LONE STAR DS 6H41													
Tire	Engine	Trans Type	Transmission	Axle	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
							Total	Front	Rear	Front	Rear		
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,700	1,610	5,198	3,012	2,186	3,380	3,900	12,500	7,100
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,700	1,610	5,198	3,012	2,186	3,380	3,900	12,500	7,100
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,700	1,610	5,198	3,012	2,186	3,380	3,900	12,500	7,100
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,700	1,610	5,198	3,012	2,186	3,380	3,900	12,500	7,100
P275/60R20	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,700	1,610	5,241	3,036	2,204	3,380	3,900	12,500	7,050
P275/60R20	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,700	1,610	5,241	3,036	2,204	3,380	3,900	12,500	7,050
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,700	1,610	5,248	3,068	2,180	3,900	3,900	14,000	8,550
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,700	1,610	5,248	3,068	2,180	3,900	3,900	15,500	10,050
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,700	1,430	5,248	3,068	2,180	3,900	3,900	14,000	8,550
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,700	1,430	5,248	3,068	2,180	3,900	3,900	15,500	10,050
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,700	1,380	5,291	3,093	2,199	3,900	3,900	14,000	8,500
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,700	1,380	5,291	3,093	2,199	3,900	3,900	15,500	10,000
Quad Cab 4x4 - SPORT DS 6S41													
Tire	Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
							Total	Front	Rear	Front	Rear		
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,700	1,610	5,343	3,107	2,235	3,900	3,900	14,000	8,450
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,700	1,610	5,343	3,107	2,235	3,900	3,900	15,500	9,950
Quad Cab 4x4 - LARAMIE DS 6P41													
Tire	Engine	Trans Type	Transmission	Axle	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
							Total	Front	Rear	Front	Rear		
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,700	1,610	5,501	3,173	2,327	3,900	3,900	14,000	8,300
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,700	1,610	5,501	3,173	2,327	3,900	3,900	15,500	9,800
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,700	1,610	5,501	3,173	2,327	3,900	3,900	14,000	8,300
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,700	1,610	5,501	3,173	2,327	3,900	3,900	15,500	9,800
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,700	1,570	5,436	3,146	2,290	3,900	3,900	14,000	8,350
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,700	1,570	5,436	3,146	2,290	3,900	3,900	15,500	9,850

NOTES:

Note that all the payload and Max Trail weights are ESTIMATED values.

1. Payload is rounded down to the nearest 10 lbs. Payload = GVWR - Curb Wt.
2. Maximum trailer weights are rounded down to the nearest 50 lbs.
 Maximum Trailer Weight = GCWR - Curb wt. -150 lbs. (allowance for driver) - 20 lbs. (variation allowance)
3. The recommended tongue weight is between 10 percent and 15 percent of the gross trailer weight. However, the maximum tongue weight on Class III (the bumper ball) is limited to 500 pounds, and Class IV (the receiver hitch) to 1,045 pounds. Additionally, the GAWR's and GVWR's should never be exceeded.
4. The maximum trailer weight is 5,000 pounds for a weight-carrying hitch. A weight distributing system is recommended for trailers over 5,000 pounds.



2011 RAM BASE WEIGHTS/GCW/PAYLOAD 1500

09/01/2010

**NOTE : BASE WEIGHTS CAN CHANGE
CREW CAB 140.5"WB 4X2**

Crew Cab 4x2 - ST											DS 1L98				
Tire	Engine	Trans Type	Transmission	Axle	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer		
							Total	Front	Rear	Front	Rear				
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGO) 5 SPD AUTO	3.55	6,800	1,700	5,070	2,861	2,210	3,700	3,900	12,500	7,250		
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGO) 5 SPD AUTO	3.92	6,800	1,700	5,070	2,861	2,210	3,700	3,900	12,500	7,250		
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGO) 5 SPD AUTO	3.55	6,800	1,700	5,070	2,861	2,210	3,700	3,900	12,500	7,250		
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGO) 5 SPD AUTO	3.92	6,800	1,700	5,070	2,861	2,210	3,700	3,900	12,500	7,250		
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGO) 5 SPD AUTO	3.21	6,800	1,670	5,107	2,906	2,202	3,700	3,900	12,000	6,700		
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGO) 5 SPD AUTO	3.55	6,800	1,670	5,107	2,906	2,202	3,700	3,900	14,000	8,700		
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGO) 5 SPD AUTO	3.92	6,800	1,670	5,107	2,906	2,202	3,700	3,900	15,500	10,200		
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGO) 5 SPD AUTO	3.21	6,800	1,670	5,107	2,906	2,202	3,700	3,900	12,000	6,700		
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGO) 5 SPD AUTO	3.55	6,800	1,670	5,107	2,906	2,202	3,700	3,900	14,000	8,700		
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGO) 5 SPD AUTO	3.92	6,800	1,670	5,107	2,906	2,202	3,700	3,900	15,500	10,200		
Crew Cab 4x2 - SLT/ TRX / BIG HORN / LONE STAR											DS 1H98				
Tire	Engine	Trans Type	Transmission	Axle	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer		
							Total	Front	Rear	Front	Rear				
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGO) 5 SPD AUTO	3.55	6,800	1,640	5,137	2,896	2,241	3,700	3,900	12,500	7,150		
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGO) 5 SPD AUTO	3.92	6,800	1,640	5,137	2,896	2,241	3,700	3,900	12,500	7,150		
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGO) 5 SPD AUTO	3.55	6,800	1,640	5,137	2,896	2,241	3,700	3,900	12,500	7,150		
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGO) 5 SPD AUTO	3.92	6,800	1,640	5,137	2,896	2,241	3,700	3,900	12,500	7,150		
P275/60R20	4.7L V8 (EVE)	A5	545RFE (DGO) 5 SPD AUTO	3.55	6,800	1,680	5,092	2,879	2,213	3,700	3,900	12,500	7,200		
P275/60R20	4.7L V8 (EVE)	A5	545RFE (DGO) 5 SPD AUTO	3.92	6,800	1,680	5,092	2,879	2,213	3,700	3,900	12,500	7,200		
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGO) 5 SPD AUTO	3.21	6,800	1,600	5,173	2,940	2,233	3,700	3,900	12,000	6,650		
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGO) 5 SPD AUTO	3.55	6,800	1,600	5,173	2,940	2,233	3,700	3,900	14,000	8,650		
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGO) 5 SPD AUTO	3.92	6,800	1,600	5,173	2,940	2,233	3,700	3,900	15,500	10,150		
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGO) 5 SPD AUTO	3.21	6,800	1,600	5,173	2,940	2,233	3,700	3,900	12,000	6,650		
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGO) 5 SPD AUTO	3.55	6,800	1,600	5,173	2,940	2,233	3,700	3,900	14,000	8,650		
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGO) 5 SPD AUTO	3.92	6,800	1,600	5,173	2,940	2,233	3,700	3,900	15,500	10,150		
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGO) 5 SPD AUTO	3.21	6,800	1,650	5,129	2,923	2,205	3,700	3,900	12,000	6,700		
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGO) 5 SPD AUTO	3.55	6,800	1,650	5,129	2,923	2,205	3,700	3,900	14,000	8,700		
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGO) 5 SPD AUTO	3.92	6,800	1,650	5,129	2,923	2,205	3,700	3,900	15,500	10,200		
Crew Cab 4x2 - SPORT											DS 1S98				
Tire	Engine	Trans Type	Transmission	Axle	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer		
							Total	Front	Rear	Front	Rear				
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGO) 5 SPD AUTO	3.21	6,800	1,540	5,235	2,950	2,285	3,700	3,900	12,000	6,550		
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGO) 5 SPD AUTO	3.55	6,800	1,540	5,235	2,950	2,285	3,700	3,900	14,000	8,550		
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGO) 5 SPD AUTO	3.92	6,800	1,540	5,235	2,950	2,285	3,700	3,900	15,500	10,050		
Crew Cab 4x2 - LARAMIE											DS 1P98				
Tire	Engine	Trans Type	Transmission	Axle	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer		
							Total	Front	Rear	Front	Rear				
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGO) 5 SPD AUTO	3.21	6,800	1,470	5,309	3,002	2,307	3,700	3,900	12,000	6,500		
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGO) 5 SPD AUTO	3.55	6,800	1,470	5,309	3,002	2,307	3,700	3,900	14,000	8,500		
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGO) 5 SPD AUTO	3.92	6,800	1,470	5,309	3,002	2,307	3,700	3,900	15,500	10,000		
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGO) 5 SPD AUTO	3.21	6,800	1,470	5,309	3,002	2,307	3,700	3,900	12,000	6,500		
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGO) 5 SPD AUTO	3.55	6,800	1,470	5,309	3,002	2,307	3,700	3,900	14,000	8,500		
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGO) 5 SPD AUTO	3.92	6,800	1,470	5,309	3,002	2,307	3,700	3,900	15,500	10,000		
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGO) 5 SPD AUTO	3.21	6,800	1,400	5,373	3,029	2,344	3,700	3,900	12,000	6,450		
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGO) 5 SPD AUTO	3.55	6,800	1,400	5,373	3,029	2,344	3,700	3,900	14,000	8,450		
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGO) 5 SPD AUTO	3.92	6,800	1,400	5,373	3,029	2,344	3,700	3,900	15,500	9,950		
Crew Cab 4x2 - PREMIUM											DS 1R98				
Tire	Engine	Trans Type	Transmission	Axle	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer		
							Total	Front	Rear	Front	Rear				
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGO) 5 SPD AUTO	3.21	6,800	1,440	5,333	3,008	2,325	3,700	3,900	12,000	6,450		
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGO) 5 SPD AUTO	3.55	6,800	1,440	5,333	3,008	2,325	3,700	3,900	14,000	8,450		
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGO) 5 SPD AUTO	3.92	6,800	1,440	5,333	3,008	2,325	3,700	3,900	15,500	9,950		

NOTES:

- Note that all the payload and Max Trail weights are ESTIMATED values.
1. Payload is rounded down to the nearest 10 lbs. Payload = GVWR - Curb Wt.
 2. Maximum trailer weights are rounded down to the nearest 50 lbs.
Maximum Trailer Weight = GCWR - Curb wt. -150 lbs. (allowance for driver) - 20 lbs. (variation allowance)
 3. The recommended tongue weight is between 10 percent and 15 percent of the gross trailer weight. However, the maximum tongue weight on Class III (the bumper ball) is limited to 500 pounds, and Class IV (the receiver hitch) to 1,045 pounds. Additionally, the GAWR's and GVWR's should never be exceeded.
 4. The maximum trailer weight is 5,000 pounds for a weight-carrying hitch. A weight distributing system is recommended for trailers over 5,000 pounds.



2011 RAM BASE WEIGHTS/GCW/PAYLOAD 1500

NOTE : BASE WEIGHTS CAN CHANGE
CREW CAB 140.5"WB 4x4

Crew Cab 4x4 - ST							DS 6L98						
Tire	Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
							Total	Front	Rear	Front	Rear		
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,530	5,240	3,006	2,234	3,900	3,900	12,500	7,050
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,530	5,240	3,006	2,234	3,900	3,900	12,500	7,050
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,530	5,240	3,006	2,234	3,900	3,900	12,500	7,050
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,530	5,240	3,006	2,234	3,900	3,900	12,500	7,050
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,500	5,278	3,052	2,226	3,900	3,900	14,000	8,550
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,500	5,278	3,052	2,226	3,900	3,900	15,500	10,050
Crew Cab 4x4 - SLT / TRX / BIG HORN / LONE STAR							DS 6H98						
Tire	Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
							Total	Front	Rear	Front	Rear		
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,520	5,255	3,019	2,237	3,900	3,900	12,500	7,050
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,520	5,255	3,019	2,237	3,900	3,900	12,500	7,050
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,520	5,255	3,019	2,237	3,900	3,900	12,500	7,050
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,520	5,255	3,019	2,237	3,900	3,900	12,500	7,050
P275/60R20	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,480	5,298	3,043	2,255	3,900	3,900	12,500	7,000
P275/60R20	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,480	5,298	3,043	2,255	3,900	3,900	12,500	7,000
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,480	5,293	3,064	2,229	3,900	3,900	14,000	8,500
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,480	5,293	3,064	2,229	3,900	3,900	15,500	10,000
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,480	5,293	3,064	2,229	3,900	3,900	14,000	8,500
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,480	5,293	3,064	2,229	3,900	3,900	15,500	10,000
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,440	5,336	3,088	2,248	3,900	3,900	14,000	8,450
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,440	5,336	3,088	2,248	3,900	3,900	15,500	9,950
Crew Cab 4x4 - SPORT							DS 6S98						
Tire	Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
							Total	Front	Rear	Front	Rear		
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,270	5,508	3,154	2,354	3,900	3,900	14,000	8,300
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,270	5,508	3,154	2,354	3,900	3,900	15,500	9,800
Crew Cab 4x4 - LARAMIE							DS 6P98						
Tire	Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
							Total	Front	Rear	Front	Rear		
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,300	5,473	3,142	2,331	3,900	3,900	14,000	8,350
LT275/70R17C	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,300	5,473	3,142	2,331	3,900	3,900	15,500	9,850
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,300	5,473	3,142	2,331	3,900	3,900	14,000	8,350
P265/70R17	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,300	5,473	3,142	2,331	3,900	3,900	15,500	9,850
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,240	5,538	3,170	2,368	3,900	3,900	14,000	8,250
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,240	5,538	3,170	2,368	3,900	3,900	15,500	9,750
Crew Cab 4x4 - PREMIUM							DS 6R98						
Tire	Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
							Total	Front	Rear	Front	Rear		
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,340	5,431	3,008	2,423	3,900	3,900	14,000	8,350
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,340	5,431	3,008	2,423	3,900	3,900	15,500	9,850

NOTES:
 Note that all the payload and Max Trail weights are ESTIMATED values.
 1. Payload is rounded down to the nearest 10 lbs. Payload = GVWR - Curb Wt.
 2. Maximum trailer weights are rounded down to the nearest 50 lbs.
 Maximum Trailer Weight = GCWR - Curb wt. -150 lbs. (allowance for driver) - 20 lbs. (variation allowance)
 3. The recommended tongue weight is between 10 percent and 15 percent of the gross trailer weight. However, the maximum tongue weight on Class III (the bumper ball) is limited to 500 pounds, and Class IV (the receiver hitch) to 1,045 pounds. Additionally, the GAWR's and GVWR's should never be exceeded.
 4. The maximum trailer weight is 5,000 pounds for a weight-carrying hitch. A weight distributing system is recommended for trailers over 5,000 pounds.



2011 RAM BASE WEIGHTS/GCW/PAYLOAD 1500

NOTE : BASE WEIGHTS CAN CHANGE

CREW CAB 140.5"WB 4X2 WITH RAM BOX

Crew Cab 4x2 w/ Rambox -SLT-TRX-BIG HORN-LONE STAR DS 1H98													
Tire	Engine	Trans Type	Transmission	Axle	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
							Total	Front	Rear	Front	Rear		
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,580	5,190	2,879	2,312	3,700	3,900	12,500	7,100
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,580	5,190	2,879	2,312	3,700	3,900	12,500	7,100
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,580	5,190	2,879	2,312	3,700	3,900	12,500	7,100
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,580	5,190	2,879	2,312	3,700	3,900	12,500	7,100
P275/60R20	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,540	5,233	2,903	2,330	3,700	3,900	12,500	7,050
P275/60R20	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,540	5,233	2,903	2,330	3,700	3,900	12,500	7,050
LT275/70R17C	5.7L V8 (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.21	6,800	1,550	5,227	2,923	2,304	3,700	3,900	12,000	6,600
LT275/70R17C	5.7L V8 (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,550	5,227	2,923	2,304	3,700	3,900	14,000	8,600
LT275/70R17C	5.7L V8 (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,550	5,227	2,923	2,304	3,700	3,900	15,500	10,100
P265/70R17	5.7L V8 (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.21	6,800	1,550	5,227	2,923	2,304	3,700	3,900	12,000	6,600
P265/70R17	5.7L V8 (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,550	5,227	2,923	2,304	3,700	3,900	14,000	8,600
P265/70R17	5.7L V8 (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,550	5,227	2,923	2,304	3,700	3,900	15,500	10,100
P275/60R20	5.7L V8 (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.21	6,800	1,510	5,270	2,948	2,322	3,700	3,900	12,000	6,550
P275/60R20	5.7L V8 (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,510	5,270	2,948	2,322	3,700	3,900	14,000	8,550
P275/60R20	5.7L V8 (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,510	5,270	2,948	2,322	3,700	3,900	15,500	10,050
Crew Cab 4x2 w/ Rambox - SPORT DS 1S98													
Tire	Engine	Trans Type	Transmission	Axle	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
							Total	Front	Rear	Front	Rear		
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.21	6,800	1,440	5,334	2,950	2,383	3,700	3,900	12,000	6,450
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,440	5,334	2,950	2,383	3,700	3,900	14,000	8,450
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,440	5,334	2,950	2,383	3,700	3,900	15,500	9,950
Crew Cab w/ Rambox 4x2 - LARAMIE DS 1P98													
Tire	Engine	Trans Type	Transmission	Axle	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
							Total	Front	Rear	Front	Rear		
LT275/70R17C	5.7L V8 (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.21	6,600	1,210	5,369	2,979	2,389	3,700	3,900	12,000	6,450
LT275/70R17C	5.7L V8 (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,600	1,210	5,369	2,979	2,389	3,700	3,900	14,000	8,450
LT275/70R17C	5.7L V8 (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,600	1,210	5,369	2,979	2,389	3,700	3,900	15,500	9,950
P265/70R17	5.7L V8 (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.21	6,800	1,410	5,369	2,979	2,389	3,700	3,900	12,000	6,450
P265/70R17	5.7L V8 (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,410	5,369	2,979	2,389	3,700	3,900	14,000	8,450
P265/70R17	5.7L V8 (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,410	5,369	2,979	2,389	3,700	3,900	15,500	9,950
P275/60R20	5.7L V8 (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.21	6,800	1,370	5,407	3,002	2,405	3,700	3,900	12,000	6,400
P275/60R20	5.7L V8 (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,370	5,407	3,002	2,405	3,700	3,900	14,000	8,400
P275/60R20	5.7L V8 (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,370	5,407	3,002	2,405	3,700	3,900	15,500	9,900
Crew Cab w/ Rambox 4x2 - PREMIUM DS 1R98													
Tire	Engine	Trans Type	Transmission	Axle	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
							Total	Front	Rear	Front	Rear		
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.21	6,800	1,340	5,431	3,008	2,423	3,700	3,900	12,000	6,350
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,340	5,431	3,008	2,423	3,700	3,900	14,000	8,350
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,340	5,431	3,008	2,423	3,700	3,900	15,500	9,850

NOTES:

Note that all the payload and Max Trail weights are ESTIMATED values.

1. Payload is rounded down to the nearest 10 lbs. Payload = GVWR - Curb Wt.
2. Maximum trailer weights are rounded down to the nearest 50 lbs.
Maximum Trailer Weight = GCWR - Curb wt. -150 lbs. (allowance for driver) - 20 lbs. (variation allowance)
3. The recommended tongue weight is between 10 percent and 15 percent of the gross trailer weight. However, the maximum tongue weight on Class III (the bumper ball) is limited to 500 pounds, and Class IV (the receiver hitch) to 1,045 pounds. Additionally, the GAWR's and GVWR's should never be exceeded.
4. The maximum trailer weight is 5,000 pounds for a weight-carrying hitch. A weight distributing system is recommended for trailers over 5,000 pounds.



2011 RAM BASE WEIGHTS/GCW/PAYLOAD 1500

NOTE : BASE WEIGHTS CAN CHANGE

CREW CAB 140.5"WB 4x4 WITH RAM BOX

Crew Cab 4x4 w/ Rambox -SLT-TRX-BIG HORN-LONE STAR DS 6H98													
Tire	Engine	Trans Type	Transmission	Axle	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
							Total	Front	Rear	Front	Rear		
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,420	5,354	3,019	2,335	3,900	3,900	12,500	6,950
LT275/70R17C	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,420	5,354	3,019	2,335	3,900	3,900	12,500	6,950
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,420	5,354	3,019	2,335	3,900	3,900	12,500	6,950
P265/70R17	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,420	5,354	3,019	2,335	3,900	3,900	12,500	6,950
P275/60R20	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,380	5,397	3,043	2,354	3,900	3,900	12,500	6,900
P275/60R20	4.7L V8 (EVE)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,380	5,397	3,043	2,354	3,900	3,900	12,500	6,900
LT275/70R17C	5.7L V8 (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,380	5,391	3,064	2,328	3,900	3,900	14,000	8,400
LT275/70R17C	5.7L V8 (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,380	5,391	3,064	2,328	3,900	3,900	15,500	9,900
P265/70R17	5.7L V8 (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,380	5,391	3,064	2,328	3,900	3,900	14,000	8,400
P265/70R17	5.7L V8 (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,380	5,391	3,064	2,328	3,900	3,900	15,500	9,900
P275/60R20	5.7L V8 (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,340	5,434	3,088	2,346	3,900	3,900	14,000	8,350
P275/60R20	5.7L V8 (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,340	5,434	3,088	2,346	3,900	3,900	15,500	9,850

Crew Cab w/ Rambox 4x4 - SPORT DS 6S98													
Tire	Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
							Total	Front	Rear	Front	Rear		
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,270	5,505	3,100	2,405	3,900	3,900	14,000	8,300
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,270	5,505	3,100	2,405	3,900	3,900	15,500	9,800

Crew Cab w/Rambox 4x4 - LARAMIE DS 6P98													
Tire	Engine	Trans Type	Transmission	Axle	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
							Total	Front	Rear	Front	Rear		
LT275/70R17C	5.7L V8 (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,240	5,533	3,120	2,413	3,900	3,900	14,000	8,250
LT275/70R17C	5.7L V8 (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,240	5,533	3,120	2,413	3,900	3,900	15,500	9,750
P265/70R17	5.7L V8 (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,240	5,533	3,120	2,413	3,900	3,900	14,000	8,250
P265/70R17	5.7L V8 (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,240	5,533	3,120	2,413	3,900	3,900	15,500	9,750
P275/60R20	5.7L V8 (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,200	5,572	3,142	2,429	3,900	3,900	14,000	8,250
P275/60R20	5.7L V8 (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,200	5,572	3,142	2,429	3,900	3,900	15,500	9,750

Crew Cab 4x4 - PREMIUM DS 6R98													
Tire	Engine	Trans Type	Transmission	Axle	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
							Total	Front	Rear	Front	Rear		
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.55	6,800	1,170	5,606	3,154	2,452	3,900	3,900	14,000	8,200
P275/60R20	5.7L V8 Hemi (EZH)	A5	545RFE (DGQ) 5 SPD AUTO	3.92	6,800	1,170	5,606	3,154	2,452	3,900	3,900	15,500	9,700

NOTES:

Note that all the payload and Max Trail weights are ESTIMATED values.

1. Payload is rounded down to the nearest 10 lbs. Payload = GVWR - Curb Wt.

2. Maximum trailer weights are rounded down to the nearest 50 lbs.

Maximum Trailer Weight = GCWR - Curb wt. -150 lbs. (allowance for driver) - 20 lbs. (variation allowance)

3. The recommended tongue weight is between 10 percent and 15 percent of the gross trailer weight. However, the maximum tongue weight on Class III (the bumper ball) is limited to 500 pounds, and Class IV (the receiver hitch) to 1,045 pounds. Additionally, the GAWR's and GVWR's should never be exceeded.

4. The maximum trailer weight is 5,000 pounds for a weight-carrying hitch. A weight distributing system is recommended for trailers over 5,000 pounds.

